

CYCLE 2026-01

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

CN code	TARIC	Reference Mail	Working Number	Description	Quotas	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
2920 29 00		2171443/2025	1329	Fosetyl-sodium (CAS RN 39148-16-8) in aqueous solution with a fosetyl-sodium content (CAS RN 39148-16-8) of 39 but not more than 41 w/w	<u>Q/521tonnes</u> <u>01.01-31.12</u>	New	UNDER EXAMINATION	DE	Applicant	Round 2026.1 to be used in the production of plant protection product (fungicide)
2921 41 00		2376650/2025	1318	Aniline with a purity of 99 % by weight or more	<u>Q/50000tonnes</u> <u>01.01-31.12</u>	New	UNDER EXAMINATION	DE DE	Applicant Opposed	Round 2026.1 used in the production of methylenediphenyl diisocyanate for manufacturing polyurethanes
2922 19 00		2510155/2025	1331	Triisopropanolamine (Tipa) with a purity by weight of 85 % or more (CAS RN 122-20-3)	<u>Q/7568000kilograms</u> <u>01.01-31.12</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026.1 to be used in the cement industry
3907 29 20		2365539/2025	1316	Polyether Polyol compromising sucrose starters modified with sorbitol, DEG and palm oil as a mixture by weight of: - Propoxylated sucrose 50 % or more but not more than 70 % (CAS RN 9049-71-2)	<u>Q/28200000kilograms</u> <u>01.01-31.12</u>	New	UNDER EXAMINATION	TR	Applicant	Round 2026.1 to be used in the formulation of Polyurethane Foam

7601 20 30 7601 20 40		275125/2013 PROLONG 2019 PROLONG 2024 PROLONG 2025	5107	Slabs and billets of unwrought aluminium alloys	<u>Q/573000tonne</u> <u>s. 01.01-31.12</u>	Amendment	UNDER EXAMINATION	EU EU	Applicant Opposed	Round 2026-01 - review of the measure.
ex 9029 20 31 ex 9029 90 00	40 40	3033673/2014	5126	CZ new proposal: Clustered instrument panel with: - or without stepping motors, - analog or digital pointers and dials, - or without microprocessor control board, - or without LED indicators or LCD display, - showing at least: - speed, - engine revolutions, - engine temperature, - the fuel level, - communicating via CAN+BUS and/or K-LINE protocols, for use in the manufacture of goods of Chapter 87 --- Current description: Clustered instrument panel with: - stepping motors, - analog pointers and dials,	<u>Q/160000piece</u> <u>s. 01.01-31.12</u>	Amendment	UNDER EXAMINATION	SK	Applicant	Round 2026-01 request for amendment.//

[illegible]

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or New request	Measure status	Partner Position Country	Partner Position	Public Comments
2811 22 00		2410551/2025	1320	Silicon dioxide with a purity by weight of 98 % or more CAS RN 112926-00-8	S	New	UNDER EXAMINATION	RO	Applicant	Round 2026/01: to be used in tyre production
2827 49 90		2073341/2025	1019	Zirconium dichloride oxide (CAS RN 7699-43-6) of a purity by weight of 95 % or more	S	New	UNDER EXAMINATION	AT	Applicant	Round 2026/01: For use in the production of bioceramics
2903 29 00		1710781/2025	1002	trans-1,2-Dichloroethylene (CAS RN 156-60-5) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION	FR	Applicant	Round 2026/01: used in the manufacture of cleaning solvents
2905 39 95		2159167/2025	1020	Propane-1,3-diol (CAS RN 504-63-2) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION	BE	Applicant	Round 2026/01: For use in the production of refrigerants, heat transfer fluids
2905 39 95		2030799/2025	1015	2,5,7,10,11,14-hexaoxa-1,6-distibabicyclo[4.4.4]tridecane (CAS RN 29736-75-2) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2026/01: Used in the production of PET (polyethylene terephthalate)
2906 29 00		1964394/2025	1012	(2-Bromo-5-iodophenyl)methanol (CAS RN 946525-30-0) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2026/01: For use in the pharmaceutical industry
2912 49 00		1792518/2025	1005	5-(1,1-Dimethylethyl)-2-methoxybenzaldehyde (CAS RN 85943-26-6) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2026/01: Used in the manufacture of pharmaceutical ingredients
2914 50 00		1939427/2025	1011	7-hydroxy-3,4-dihydronaphthalen-1(2H)-one (CAS RN 22009-38-7) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2026/01: For use in the pharmaceutical

2916 14 00			2278312/2025		1031		2-Hydroxyethyl methacrylate (CAS RN 868-77-9) with a purity by weight of 97 % or more	S			New	UNDER EXAMINATION	NL	Applicant	Round 2026/01: Used in the production of polymers
2917 12 00			2171718/2025		1026		Bis(3,4-epoxycyclohexylmethyl)adipate (CAS RN 3130-19-6) of a purity by weight of 97 % or more	S			New	UNDER EXAMINATION	DE	Applicant	Round 2026/01: Used for coating, ink and composite applications
2917 19 80			2168744/2025		1025		Dibutyl itaconate (CAS RN 2155-60-4) with a purity of 96 % by weight or more	S			New	UNDER EXAMINATION	NL	Applicant	Round 2026/01: Used in the production of coating resins
2917 20 00			2481545/2025		1033		1,2,3,6-Tetrahydrophthalic anhydride (CAS RN 85-43-8) with a purity by weight of 98 % or more	S			New	UNDER EXAMINATION	NL	Applicant	Round 2026/01: For use as an intermediate for polyesters, plasticizers, adhesives, and as a hardener for resins
2918 29 00			1898599/2025		1008		3-hydroxy-2-naphthoic acid (CAS RN 92-70-6) with a purity by weight of 99 % or more	S			New	UNDER EXAMINATION	ES	Applicant	Round 2026/01: Used in the pharmaceutical industry
2918 30 00			2272516/2025		1030		2-(4-Chlorobenzoyl)benzoic acid (CAS RN 85-56-3) with a purity by weight of 99 % or more	S			New	UNDER EXAMINATION	NL	Applicant	Round 2026/01: For use in the resins & polymer industry
2918 30 00			2204124/2025		1029		Prohexadione-calcium (ISOM) (CAS RN 127277-53-6) with a purity by weight of 95 % or more	S			New	UNDER EXAMINATION	NL	Applicant	Round 2026/01: For use as plant growth regulator
2918 99 90			2366645/2025		1317		methyl-3-methoxyacrylate with a purity by weight of 98 % or more CAS RN 5788-17-0	S			New	UNDER EXAMINATION	FI	Applicant	Round 2026.1 to be used for the materials to produce crop protection products

2918 99 90		2171914/2025	1027	3,4-Epoxy-cyclohexyl-methyl-3',4'-epoxy-cyclohexane carboxylate (CAS RN 2386-87-0) of a purity by weight of 91 % or more	S	New	UNDER EXAMINATION	DE	Applicant	Round 2026/01: used for UV-curing coatings, inks and composite applications
2920 29 00		2312786/2025	1315	Tris(2-chloroethyl) phosphite (CAS RN 140-08-9) with a purity by weight of 90 % or more	S	New	UNDER EXAMINATION	NL	Applicant	Round 2026.1 used as a flame retardant additive
2922 29 00		2065421/2025	1017	4-Amino-2,3-dichlorophenol (CAS RN 39183-17-0) with a purity by weight by 98 % or more	S	New	UNDER EXAMINATION	DE	Applicant	Round 2026/01: Used in the production of plant protection products
2922 49 85		2189820/2025	1028	Magnesium-2-aminoacetate (CAS RN 14783-68-7) with a purity by weight of 100 %, imported in packages not less than 25Kg; not put up for retail sale	S	New	UNDER EXAMINATION	IE	Applicant	Round 2026/01: for use in the health food and supplement industry
2923 10 00		2029862/2025	1014	Calcium Phosphoryl Choline Chloride (CAS RN 72556-74-2) with a purity by weight of 90 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2026/01: For use in the pharmaceutical industry
2924 29 70		1902090/2025	1009	Calcium bis[(2 <i>r</i> ,4 <i>s</i>)-5-(biphenyl-4-yl)-4-(3-carboxypropionylamino)-2-methylpentanoic acid ethyl ester)] salt with a purity by weight of 98,0 % or more	S	New	UNDER EXAMINATION	SI IE	Applicant Co-applicant	Round 2026/01: Used in the pharmaceutical industry
2925 29 00		2166771/2025	1023	N-amidinosarcosine hydrate (CAS 6020-87-7) with a purity by weight of 99 % or more, imported in packages not less than 25 kg	S	New	UNDER EXAMINATION	IE	Applicant	Round 2026/01: For use in the health food and supplement industry
2926 90 70		1713491/2025	1003	2,3,3,3-Tetrafluoro-2-(trifluoromethyl)propanenitrile (CAS RN 42532-60-5) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION	FR	Applicant	Round 2026/01: used as inert gas for the insulation of high voltage installation
2926 90 70		1790113/2025	1004	3,4-dimethoxybicyclo[4.2.0]octa-1,3,5,-triene-7-carbonitrile (CAS RN 35202-54-1)	S	New	UNDER EXAMINATION	ES	Applicant	Round 2026/01: for use in the

2931 90 00			2163644/2025	1021	with a purity by weight of 97 % or more	S	New	UNDER EXAMINATION	AT	Applicant	pharmaceutical industry
					F3 – Catalyst of an organic hafnium compound in powder form (CAS RN 264926-41-2) or dissolved in hexane (CAS RN 657-27-2) with a purity of 95 % or more						Round 2026/01: For use in the production of polyethylene
2931 90 00			2164499/2025	1022	Hydrogen tetrakis(pentafluorophenyl)borate(1-)-N,N-dimethylaniline (1:1) (CAS RN 118612-00-3) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION	AT	Applicant	Round 2026/01: For use in the production of polyethylene
2932 20 90			2168134/2025	1024	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide (CAS RN 1552-42-7) with a purity by weight of 96 % or more	S	New	UNDER EXAMINATION	NL	Applicant	Round 2026/01: Used in the manufacturing of carbonless copy paper
2933 39 99			1793363/2025	1006	(1R,2S,4R)-2-Benzhydrylquinclidin-3-one (2R,3R)-2,3-dihydroxysuccinate (CAS RN 683206-54-4) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2026/01: Used in the production of pharmaceutical ingredients
2933 99 80			1793936/2025	1007	(2R,3R)-2-(2,4-Difluorophenyl)-1-(1H-1,2,4-triazol-1-yl)butane-2,3-diol methanesulfonate (CAS RN 1175536-50-1) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2026/01: Used in the production of pharmaceutical ingredients
2934 99 90			2028227/2025	1013	Sodium uridine-5'-monophosphate (CAS RN 3387-36-8) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2026/01: For use in the manufacture of food supplement products
2934 99 90			2057866/2025	1016	Nedosisran Sodium (CAS RN 2247026-22-6) with a purity by weight of 95 % or more	S	New	UNDER EXAMINATION	DK	Applicant	Round 2026/01: For use in the pharmaceutical industry
2934 99 90			1790941/2025	1001	[6R-[6 α ,7B(Z)]]-7-[2-furyl(methoxyimino)acetamido]-3-	S	New	UNDER EXAMINATION	IT	Applicant	Round 2026/01: used in the

3808 99 90			1697141/2025	1000	(hydroxymethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 56271-94-4) with a purity by weight of 96 % or more	S		New	UNDER EXAMINATION	FR	Applicant	Round 2026/01: Used for the manufacture of deworming for dogs and cats	manufacturing of antibiotics
3812 10 00			2486402/2025	1035	TBBSI - Rubber vulcanizing agent consisting of a light white to light yellow-brown powder, the product is a preparation, with the following components: - N-(1,1-dimethylethyl) bis(2-benzothiazolesulfen) amide (CAS RN 3741-80-8) with a purity by weight of 98 % or more and - White mineral oil (petroleum) (CAS RN 8042-47-5) with a purity by weight of 2 % or more	S		New	UNDER EXAMINATION	RO	Applicant	Round 2026/01: Used in the manufacture of tyres	
3824 99 92			2483059/2025	1034	Trimethylolpropane ethoxylate (CAS RN 50586-59-9)	S		New	UNDER EXAMINATION	NL	Applicant	Round 2026/01: Used in the production of polymers	
3824 99 92			2279213/2025	1032	Mixture of primary tert-alkylamines (CAS RN 68955-53-3)	S		New	UNDER EXAMINATION	DE	Applicant	Round 2026/01: For use in the production of phosphoric acid ester	
3824 99 92			1903259/2025	1010	Pentanoic acid, 5-(dimethylamino)-2-methyl-5-oxo-methyl ester (CAS RN 1174627-68-9) with a purity by weight of 75 % or more	S		New	UNDER EXAMINATION	FR	Applicant	Round 2026/01: Used in the production of plant protection products	
3824 99 96			2072871/2025	1018	Yttria Stabilized Zirconia (YSZ) (CAS RN 64417-98-7) of a purity by Zirconia of 90 % or more	S		New	UNDER EXAMINATION	AT	Applicant	Round 2026/01: Used in the production of bioceramics, structural ceramics,	

3901 10 10			2246559/2025	1310	Linear low-density polyethylene (ethylene-1-butene) (CAS RN 25087-34-7), - with a melt flow rate (MFR) 190 °C/2.16 kg) of 0.43 or more but not more than 1.00 g/10 min, - with a density (ASTM D 1505) of 0.915 g/cm³ or more, but not more than 0.942 g/cm³.	S	New	UNDER EXAMINATION	TR	Applicant	technical ceramics Round 2026.1 to be used as a raw material for flexible packaging production
3902 10 00			2277892/2025	1313	Polypropylene containing no plasticiser, - of a tensile strength: of 26 - 36 MPa (as determined by ISO 527 method), - of a melt Flow Rate (mfr) at 230 °C of 10 - 30 g/10 min (as determined by the ISO 1133 method), - of flexural modulus higher than 2300 MPa (as determined by the ISO 178 method), - with 60 % or more but not more 90 % by weight of Polypropylene, - with 10 % or more but not more than 45 % by weight of talc powder. - recycled material is above 99 % Polypropylene component coming from a single source of polypropylene recycled.	S	New	UNDER EXAMINATION	CZ	Applicant	Round 2026.1 to be used in assembling air conditioning units of vehicles
3904 69 80			2275570/2025	1312	Polyvinylidene Difluoride (PVDF) (CAS RN 24937-79-9)	S	New	UNDER EXAMINATION	TR FR	Applicant Opposed	Round 2026.1 to be used in the production of capillary membrane (hollow fiber)
3911 90 19			2225697/2025	1306	Benzenamine, 4,4'-oxybis-, polymer with 1,3-benzenediamine and 1,3-dihydro-1,3-dioxo-5-isobenzofuranecarbonyl chloride (CAS RN	S	New	UNDER EXAMINATION	BE	Applicant	Round 2026.1 to be used in the production of protective and adhesive coatings

3911 90 99			2205779/2025		1305	35463-82-2) or 5-Isobenzofurancarbonyl chloride, 1,3-dihydro-1,3-dioxo-, polymer with 4,4'-methylenebis[benzenamine] (CAS RN 25928-85-2) containing by weight not more than 35 % of additives A mixture containing by weight: - 89 % or more but not more than 91 % of 1,4,5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and - 9 % or more but not more than 11 % of Polypropylene Homopolymer (CAS RN 9003-07-0)	S		New	UNDER EXAMINATION	IE	Applicant	Round 2026.1 for use in the production of disposable contact lenses
3920 62 19			2246820/2025		1311	Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers, badges and tapes, safety clothing and accessories thereof, or of school satchels, bags or similar containers	S		New	UNDER EXAMINATION	IE	Applicant	Round 2026.1 to be used in the production of reflective safety products usually under CN 39191080 and 39199080
3921 19 00			2026850/2025		1302	Strip of microporous polytetrafluoroethylene on a support of a non-woven for use in the manufacture of filters for kidney dialysis equipment (1)	S		New	UNDER EXAMINATION	IE	Applicant	Round 2026.1 for use in the production of medical equipment
4016 99 57			2246416/2025		1309	Wiper rubber specifically designed for the manufacture of windshield wipers for motor vehicles under the tariff heading 8512 with; - a length of 300mm or more but not more than 700mm; - made of with NR CR 60 Shore A structure	S		New	UNDER EXAMINATION	TR	Applicant	Round 2026.1 to be used in vehicle wiper blades

5402 33 00		2204850/2025	1304	Textured polyester yarn: - textured using single heater and double heater methods, - with a linear density of 83 dtex or more, but not more than 666 dtex, - with an average minimum tenacity of 32 cN/tex, - with a filament count of 36 or more, but not more than 192, - with an elongation of 16 % or more, but not more than 33 %, - with a boiling water shrinkage of 3 % or more, but not more than 8 %, - with a content of preparation 1 % or more, but not more than 3 %	S		New	UNDER EXAMINATION	PL	Applicant	
5403 31 00		1835626/2025	1301	Viscose rayon filament yarn centrifugal, measuring 80 decitex or more, but not more than 88 decitex, consisting of a number of monofilaments of 24 or more, but not more than 36.	S		New	UNDER EXAMINATION	ES	Applicant	Round 2026.1 for the production of fabrics
5602 10 19		2281825/2025	1314	Needle punched felt with a polyvinyl alcohol content of 20 % or more but not more than 40 %	S		New	UNDER EXAMINATION	TR	Applicant	Round 2026.1 to be used in the manufacture of microfiber synthetic leather
5902 10 10		2235613/2025	1307	Cord fabric obtained by impregnating nylon or other polyamides with rubber containing by weight of: - 90 % or more but not more than 98 % Polyamide 6 - 2 % or more but not more than 7 % RFL (Resorcinol Formaldehyde Latex) and - 1 % or less cotton yarn for use in any type of transport vehicle tire	S		New	UNDER EXAMINATION	TR	Applicant	Round 2026.1 to be used in the production of vehicle tires

7019 80 10		2165498/2025	1303	Vacuum Insulation Panel consisting of a hermetic casing made of multi-layer foil devoid of air, used for thermal insulation of the interior of the fridge-freezer: - the main insulating material of the product is fiberglass (wool fiber) (min 70 %), - panel thickness 15 mm or more, but not more than 35 mm, - width 165 mm or more, but not more than 510 mm, - length 375 mm or more, but not more than 1875 mm, - thermal conductivity coefficient K-factor below 0.0015 kcal/(h·m·°C), - ambient temperature during operation from -50 °C or more, but not more than 80 °C	S		New	UNDER EXAMINATION	PL	Applicant	Round 2026.1 used in the production of refrigerators
8109 29 00		1835222/2025	1300	Non-alloy zirconium sponges or ingots containing by weight more than 0,01 % of hafnium for use in the manufacture of tubes, bars or ingots enlarged by remelting for the non-nuclear industry (1)	S		New	UNDER EXAMINATION	SE	Applicant	Round 2026.1 for the production of bars and tubes used in non-nuclear industry
8207 19 10		2246032/2025	1308	Inserts for drilling tools with working parts of agglomerated diamonds	S		New	UNDER EXAMINATION	TR	Applicant	Round 2026.1 to be used in PDC (Polycrystalline Diamond Compact) drill bits
8409 91 00		2947092/2025	2011	Connecting rod for connecting pistons to the crankshaft of a passenger car engine: - made of an alloy containing 96 % steel and the remainder being titanium, vanadium, aluminum, chromium, nickel, copper, phosphorus, silicon, sulfur,	S		New	UNDER EXAMINATION	PL	Applicant	Round 01/2026 - new request component for the automotive industry

8414 30 20						manganese, - with two connecting rod bolts, - with plain bearing, - of a length of 120 mm or more but not more than 160 mm, - with a surface roughness corresponding to ISO 4287-1997, for use in the manufacture of motor vehicle engines (1)	S	New	UNDER EXAMINATION	PL	Applicant	Round 2026.1 used in the production of refrigerators and fridge-freezers
8414 59 25		2446092/2025	1323			Hermetic compressor for R600a refrigerant for the production of refrigerators and fridge-freezers: - with a power not exceeding 0.4 kW, - pre-filled with mineral lubricant oil from 110 cm3 to 175 cm3, - suction and processing pipe inner diameter from 6.34 to 6.74 mm, thickness from 0.6 to 0.8 mm, - discharge pipe inner diameter from 4.9 to 5.1 mm, thickness from 0.75 to 0.95 mm, - hermetic clamp and bracket, which can be assembled with a plastic cover, - speed range from 900 rpm to 4500 rpm, - driven by a brushless DC electric motor, - cooling capacity from 76 to 110 W at 1800 rpm (1)	S	New	UNDER EXAMINATION	PT	Applicant	Round 01/2026 - new request component for the automotive industry

8414 90 00							A - an input power between: 0,3 to 1,5 W - a rotation speed between: 2500 to 10000 R.P.M. - an air flow of not more than 25 CFM (cubic foot per minute) - an air pressure of not more than 10 mmH2O - an overall sound of not more than 45 dB(A) - a diameter of not more than 65mm With or without an heat sink incorporated	S				UNDER EXAMINATION	HU	Applicant	Round 2026.1 to be incorporated in electric air conditioning compressors for motor vehicles
8418 99 90				2705253/2025	2464396/2025	1324	Evaporator, which is a type of heat exchanger used in refrigerators and refrigerators with freezers: - with an external dimensions from 362x244x60mm to 398.4x503x60 mm, - with aluminium radiators with dimensions from 60x26.7 mm to 60.2x27.3 mm, - with an aluminium tube with an external diameter of 8.4 - 8.5 mm, - with a straight internal channel or with an elongated internal channel with grooves of 40 pcs grooves,	S						Applicant	Round 01/2026 - new request component household appliance industry

8418 99 90		2727561/2025	2006	- with 229 to 307 radiating fins, - without heaters or max. with two heaters with power of 40 W or more, but not more than 140 W, - without thermal fuses or with two such fuses with a melting point of 77 °C	S	New	UNDER EXAMINATION	PL	Applicant	Round 01/2026 - new request components for domestic appliance industry
8481 80 99		2400121/2025	1319	Service valve which suits for R410A or R32 gas while connecting indoor and outdoor units with: - a withstanding pressure of the valve body of 6,3 MPa, - a leakage ratio of less than 1.6 g/a, - an impurity ratio of less than 1.2 mg/PCS, - an airtight pressure of the valve body of 4.2 Mpa for use in the manufacture of air	S	New	UNDER EXAMINATION	TR	Applicant	Round 2026.1 used as component in air conditioning systems

8483 50 80			2947464/2025	2012	conditioners (1)	S			UNDER EXAMINATION	SK	Applicant	Round 01/2026 - new request component for the automotive industry
					Flywheel for damping torsional vibrations and oscillations within the car's drivetrain: - with a total moment of inertia of 0.082 kg.m², - with a weight of 7 kg or more, but not more than 8 kg, - with a diameter of 250 mm or more, but not more than 280 mm for use in the manufacture of motor vehicles(1)							
8501 31 00			2701255/2025	2002	DC motor, brushless, integrated with an Electronic Control Unit (ECU), defined as a Power Pack with: - a safety feature and mechanism designed for prevention of critical hazards like self-steer by single failure, - a CAN-communication interface, - an external sensor interface, - operating temperature range of -40°C to 95°C or broader, - compliance with standard IP6K9K for water and dustproofness, - supply voltage of 9 V or more, but not more than 16 V, - rated power output of 500 W or more, but not higher than 750 W, - rated torque of 3 Nm or more, but not more than 6 Nm, - length of 150 mm or more, but not more than 250 mm, - width of 100 mm or more, but not more than 150 mm, - height of 80 mm or more, but not more than 120 mm	S			UNDER EXAMINATION	PL	Applicant	Round 01/2026 - new request components for the automotive industry

8501 31 00		2705655/2025	2005	Brushless DC electric motor: - with an output power of 200 W or greater, but not exceeding 700 W, - with a supply voltage of 30 V or greater, but not exceeding 60 V, - with a torque of 30 Nm or greater, but not exceeding 200 Nm, - with an outer diameter of 135 mm or greater but not exceeding 175 mm, - with a weight of 2 kg or greater but not exceeding 5 kg, - designed to be mounted in a frame, front or rear bicycle wheel, - equipped with an LCD display	S		New	UNDER EXAMINATION	PL	Applicant	Round 01/2026 - new request component for the automotive industry
8501 40 20		2946361/2025	2010	Single-phase brushless AC motor with an output not exceeding 750W, incomplete, for drum drive of washing machines and washer-dryers, consisting of rotor and stator: - rotor on the inside is equipped with a ring of 12 magnets housed in a steel casing, - stator with an internal diameter of 206.6 mm (± 0.5), external diameter of 265.0 mm (± 0.2) and width of 37.2 mm to 47.8 mm, - with a rated power not exceeding 750 W, - with a mass of 5 kg or more, used in the production of washing machines, washer-dryers equipped with a drum with direct drive	S		New	UNDER EXAMINATION	PL	Applicant	Round 01/2026 - new request component for the household appliances industry
8507 60 00		2730921/2025	2007	Rechargeable lithium-ion batteries: - with fuse, - with a battery cell design, - using LFP technology, - with a length of 1055 mm or more, but not more than 1065 mm,	S		New	UNDER EXAMINATION	PL	Applicant	Round 01/2026 new request batteries/accumulators

8507 60 00							- with a width of 630 mm or more, but not more than 640 mm, - of a height of 242 mm or more but not more than 253 mm, - of a mass of 262 kg or more but not more than 270 kg, - with a capacity of 268 Ah, - with upper outer casing made of composite material, - with IP68 protection level or more, - with energy density of 264 Wh/dm³ or higher, - with specific energy of 167 Wh/kg or higher, - without contactors, for use in the manufacture of batteries for electric buses (1)	S				UNDER EXAMINATION	ES	Applicant	Round 2026.1 to be used in electric vehicles
8507 60 00			2479524/2025	1328		Lithium-ion rechargeable batteries with: - a length of 700 mm or more, but not more than 2 820 mm, - a width of 935 mm or more, but not more than 1 660 mm, - a height of 85 mm or more, but not more than 700 mm, - a weight of 250 kg or more, but not more than 700 kg, - a power of not more than 175 kWh - a nominal voltage of 650V or more, but not more than 800V	S								
8507 60 00			2944920/2025	2009		Lithium Iron Phosphate (LFP) Blade Cell (in-line anode and cathode position to both ends of cell) with embedded anti-vibration bracket: - with a length of 110 mm or more but not more than 145.5 mm, - with a width of 40 mm or more but not more than 58.2 mm,	S					UNDER EXAMINATION	TR	Applicant	Round 01/2026 - new request batteries/accumulators

8507 60 00			2478190/2025	1326	- with a height of 401 mm or more but not more than 405.2 mm, - with a weight of 3500 gr ($\pm$ %0,5) or more but not more than 7000 gr ($\pm$ %0,5), - with a nominal Capacity of 150 Ah or more but not more than 300 Ah	S		New	UNDER EXAMINATION	BE	Applicant	Round 2026.1 for use in electric trucks
8507 60 00			2704328/2025	2003	A rechargeable lithium-ion battery, containing a fuse, in cell-to-pack design, with: - a length of 1 050 mm or more, but not more than 1 070 mm, - a width of 624 mm or more, but not more than 636 mm, - a height of 235 mm or more, but not more than 245 mm, - a mass of 214,4 kg or more, but not more than 227,6 kg, - a capacity of 228 Ah, - using LFP technology, - an upper outer casing of the battery	S		New	UNDER EXAMINATION	PL	Applicant	Round 2026-01 new request battery industry

8507 60 00			2733173/2025	2008	made of a composite material, - battery with R100.02 certificate, - protection class IP 68 (battery connected to the system), - without contactors, - with volumetric energy of 220Wh/l or higher, - gravimetric energy of 159Wh/kg or higher, for use in the manufacture of batteries for electric buses (1)	S		New	UNDER EXAMINATION	PL	Applicant	Round 01/2026 - new request batteries/accumulators
8507 60 00			2478851/2025	1327	Rechargeable lithium-ion batteries: - with fuse, - with a battery cell design, - using LFP technology, - with a length of 1345 mm or more, but not more than 1355 mm, - with a width of 655 mm or more, but not more than 665 mm, - with a height of 238 mm or more, but not more than 248 mm, - with a mass of 272 kg or more, but not more than 275 kg, - with a capacity of 95 Ah, - with upper outer casing made of composite material, - with IP68 protection level, or more, - with energy density of 135 Wh/dm3 or higher, - with specific energy of 112 Wh/kg or higher, - without contactors, for use in the manufacture of batteries for electric buses (1) A rechargeable lithium-ion battery pack, based on Lithium-iron-phosphate	S		New	UNDER EXAMINATION	BE	Applicant	Round 2026.1 to be used in electric trucks

8537 10 91			2947957/2025	2013	not more than 146 mm, - with width of 142 mm or more, but not more than 490 mm, - with a height of 93 mm or more, but not more than 100 mm, - a weight of 414 g or more, but not more than 578 g, - with lightguide	S				UNDER EXAMINATION	SK	Applicant	Round 01/2026 - new request component for the automotive industry
					Control unit for the automatic transmission oil pump for efficient cooling and oil pressure regulation in the car's drivetrain: - liquid-cooled, - with an operating voltage of 9 V DC or more, but not more than 16 V, - with a height of 165 mm or more, but not more than 190 mm, - with a width of 40 mm, but not more than 60 mm, - with a length of 170 mm or more, but not more than 195 mm, - in a casing, - with one or more connectors, and for use in the manufacture of hybrid motor vehicles (1)	S						Applicant	Round 01/2026 - new request component for the automotive industry
8549 13 20			2695775/2025	2000	Spent lithium-ion or nickel metal hydride electric accumulators	S				UNDER EXAMINATION	BE	Applicant	round 01/2026 battery industry
8708 50 99			2948134/2025	2014	Roll rod assembly for the front suspension in vehicles for connecting the stabilizer to the suspension components: - made of aluminum, rubber, and plastic, - with a height of 270 mm or more, but not more than 300 mm, - with a width of 50 mm, but not more than 65 mm, - with a length of 150 mm or more, but	S				UNDER EXAMINATION	SK	Applicant	Round 01/2026 - new request component for the automotive industry

8708 95 99			2948356/2025	2015	not more than 170 mm, for use in the manufacture of motor vehicles (1)	S	New	UNDER EXAMINATION	SK	Applicant	Round 01/2026 - New request component for the automotive industry
8708 99 97			2696943/2025	2001	The airbag assembly for enhancing safety in the event of a car collision: - with a wiring harness, - with a polyamide inflatable safety cushion, - with an inflator containing cold gas, - in a housing, - with mounting brackets for use in the manufacture of motor vehicles(1)	S	New	UNDER EXAMINATION	SK	Applicant	Round 01/2026 new request for components for the automotive industry
8714 93 00			2411868/2025	1321	Gear set without a pawl mechanism, mounted on a hub drum, connecting sprockets: - with 7 row or more sprockets, but not more than 12 row sprockets, - with 10 teeth per gear or more, but not more than 52 teeth, - with a weight of 200 g or greater, but not exceeding 800 g, - with sprockets made of nickel-plated steel or aluminium for use in the manufacture of bicycles and e- bikes (1)	S	New	UNDER EXAMINATION	PL	Applicant	Round 2026.1 to be used in the production of bicycles and e-bikes
9401 99 20			3080179/2025	2017	Cassette, a locking mechanism mounted on the seat skeleton, designed for use in the manufacture of passenger car seats	S	New	UNDER EXAMINATION	TR	Applicant	Round 01/2026 - new request component for the automotive industry

ex 2823 00 00	10	294577/2011 446/2/1995 PROLONG 2023	5105	Titanium dioxide (CAS RN 13463-67-7): - of a purity by weight of 99,9 % or more, - with an average grain-size of 0,7 µm or more but not more than 2,1 µm	S	Amendment	UNDER EXAMINATION	AT EU	Applicant Opposed	Round 2026-01 - review of the measure,
ex 2827 39 85	10	1255/2/1992 PROLONG 2019 PROLONG 2024 PROLONG 2025	5111	DE new proposal: Copper monochloride of a purity by weight of 96 % or more (CAS RN 7758-89-6) --- Current description: Copper monochloride (CAS RN 7758-89-6) of a purity by weight of 96 % or more but not more than 99 %	S	Amendment	UNDER EXAMINATION	IT	Applicant	Round 2026-01 - request for amendment.//
ex 2903 99 80	80	311432/2013 PROLONG 2019 PROLONG 2024 PROLONG 2025	5112	DE new proposal: 1-Bromo-3,4,5-trifluorobenzene (CAS RN 138526-69-9) with a purity by weight of 99 % or more --- Current description: 1-Bromo-3,4,5-trifluorobenzene (CAS RN 138526-69-9)	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 request for amendment.//
ex 2905 22 00	20	5450710/2016 PROLONG 2022	5113	DE new proposal: 3,7-Dimethyloct-6-en-1-ol (CAS RN 106-22-9) with a purity by weight of 94 % or more --- Current description: 3,7-Dimethyloct-6-en-1-ol (CAS RN 106-22-9)	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 - request for amendment.//
ex 2907 12 00	30	3078811/2014 PROLONG 2020 PROLONG 2025	5114	DE new proposal: p-Cresol (CAS RN 106-44-5) with a purity by weight of 99 % or more	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 - request for amendment.//

ex 2907 19 10	10	555815/2014 PROLONG 2020 PROLONG 2025	5119	*** Current text: p-Cresol (CAS RN 106-44-5) DE new proposal: 2,6-Xylenol (CAS RN 576-26-1) with a purity by weight of 99 % or more *** Current description: 2,6-Xylenol (CAS RN 576-26-1)	S		Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 - request for amendment.//
ex 2907 29 00	70	1747/1/2002 PROLONG 2019 PROLONG 2024 PROLONG 2025	5115	DE new proposal: 2,2',2'',6,6',6''-Hexa-tert-butyl-α,α',α''- (mesitylene-2,4,6-triyl)tri-p-kresol (CAS RN 1709-70-2) with a purity by weight of 98 % or more --- Current test: 2,2',2'',6,6',6''-Hexa-tert-butyl-α,α',α''- (mesitylene-2,4,6-triyl)tri-p-kresol (CAS RN 1709-70-2)	S		Amendment	UNDER EXAMINATION	IT	Applicant	Round 2026-01 request for amendment.//
ex 2907 29 00	75	4509689/2017 PROLONG 2019 PROLONG 2024 PROLONG 2025	5116	DE new proposal: Biphenyl-4,4'-diol (CAS RN 92-88-6) with a purity by weight of 99 % or more --- Current text: Biphenyl-4,4'-diol (CAS RN 92-88-6)	S		Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 request for amendment.//
ex 2909 30 90	30	598074/2010 PROLONG 2016 PROLONG 2021	5117	DE new proposal: 3,4,5-Trimethoxytoluene (CAS RN 6443- 69-2) with a purity by weight of 98 % or more --- Current text: 3,4,5-Trimethoxytoluene (CAS RN 6443- 69-2)	S		Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 request for amendment.//

ex 2916 39 90	70	1728/1/2002 PROLONG 2019 PROLONG 2024 PROLONG 2025	5104	DE new proposal: Ibuprofen (INN) (CAS RN 15687-27-1) with a purity by weight of 99 % or more *** Current text: Ibuprofen (INN) (CAS RN 15687-27-1)	S	Amendment	UNDER EXAMINATION	BE DE	Applicant Co-applicant	Round 2026-01 - request for amendment.
ex 2919 90 00	25	1605700/2019 PROLONG 2025	5020	Triphenyl phosphate (CAS RN 115-86-6)	S	Amendment	UNDER EXAMINATION	IT EU	Applicant Opposed	Round 2026-01 - objection.//
ex 2921 42 00	55	1692715/2019 PROLONG 2025	5118	DE new proposal: 4-chloroaniline (CAS RN 106-47-8) with a purity by weight of 99 % or more --- Current text: 4-Chloroaniline (CAS RN 106-47-8)	S	Amendment	UNDER EXAMINATION	ES	Applicant	Round 2026-01 request for amendment.//
ex 2922 19 00	35	3962047/2015 PROLONG 2021	5103	DE: 2-[2- (dimethylamino) ethoxy] ethanol (CAS RN 1704-62-7) with a purity by weight of 98 % or more *** Current text: 2-[2-(Dimethylamino)ethoxy] ethanol (CAS RN 1704-62-7)	S	Amendment	UNDER EXAMINATION	DE DE	Applicant Co-applicant	Round 2026-01 - Prolongation Exercise
ex 2930 90 95	53	1091197/2015 PROLONG 2021	5120	DE new proposal: Bis(4-chlorophenyl) sulphone (CAS RN 80- 07-9) with a purity by weight of 98 % or more --- Current description: Bis(4-chlorophenyl) sulphone (CAS RN 80- 07-9)	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 - request for amendment.//

ex 2933 19 90	25	662163/2014 PROLONG 2020 PROLONG 2025	5110	DE new proposal: 3-Difluoromethyl-1-methyl-1H-pyrazole-4-carboxylic acid (CAS RN 176969-34-9) with a purity by weight of 97 % or more --- Current description: 3-Difluoromethyl-1-methyl-1H-pyrazole-4-carboxylic acid (CAS RN 176969-34-9)	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 request for amendment.//
ex 2933 39 99	21	3081637/2014 PROLONG 2020 PROLONG 2025	5223	DE new peoposal: Boscalid (ISO) (CAS RN 188425-85-6) with a purity by weight of 98 % or more --- Current description: Boscalid (ISO) (CAS RN 188425-85-6)	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 - request for amendment.//
ex 2933 49 10	10	457/5/1998 PROLONG 2019 PROLONG 2024 PROLONG 2025	5121	DE: Quimerac (ISO) (CAS RN 90717-03-6) with a purity by weight of 98 % or more *** Current description: Quimerac (ISO) (CAS RN 90717-03-6)	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2026-01 - request for amendment.//
ex 2933 99 80	20	1412/2/1990 PROLONG 2019 PROLONG 2024 PROLONG 2025	5122	DE new proposal: 2-(2H-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol (CAS RN 70321-86-7) with a purity by weight of 99 % or more *** Current description: 2-(2H-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol (CAS RN 70321-86-7)	S	Amendment	UNDER EXAMINATION	DE	Applicant	Prolongation Exercise
ex 2934 99 90	58	1687/6/1996 PROLONG 2019	5102	DE new proposal: Dimethenamide-P (ISO) (CAS RN 163515-14-8) with a purity by weight of 93 % or	S	Amendment	UNDER EXAMINATION	DE BE FR	Applicant Co-applicant Co-applicant	Prolongation exercise

ex 3824 99 92	69	1102055/2015 PROLONG 2022	5022	- 5 % or more, but not more than 35 % of triphenyl phosphate (CAS RN 115-86-6)	S	Amendment	UNDER EXAMINATION	FR NL EU	Applicant Applicant Opposed	Round 2026-01 - objection.//
ex 3824 99 92	74	6480217/2022	5023	Preparation containing by weight: - 80 % or more but not more than 92 % of Bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5) - 7 % or more but not more than 20 % oligomers of Bisphenol-A bis(diphenyl phosphate) and - not more than 1 % triphenyl phosphate (CAS RN 115-86-6) Reaction mass containing by weight: - 22,4 % or more, but not more than 26,4 % of 3-methylphenyl diphenyl phosphate (CAS RN 69500-28-3); - 17,3 % or more, but not more than 21,3 % of 4-methylphenyl diphenyl phosphate (CAS RN 78-31-9); - 5 % or more, but not more than 9 % of bis(3-methylphenyl) phenyl phosphate (CAS RN 34909-68-7); - 8,9 % or more, but not more than 12,9 % of 3-methylphenyl 4-methylphenyl phenyl phosphate (CAS RN 222165-66-4); - 26,9 % or more, but not more than 30,9 % of triphenyl phosphate (CAS RN 115-86-6)	S	Amendment	UNDER EXAMINATION	IT EU	Applicant Opposed	Round 2026-01 - objection Component flame retardant
ex 3905 99 90	97	1728/7/2002 PROLONG 2019 PROLONG 2024	5108	DE new proposal: Povidone-iodine (CAS RN 25655-41-8) with a purity by weight of 92 % or more *** Current text: Povidone (INN)-iodine (CAS RN 25655-	S	Amendment	UNDER EXAMINATION	BE	Applicant	Round 2026-01 - Request for amendment.//

ex 3911 90 19	15	1889490/2021	5109	41-8)	NL new proposal: Polyetherimide of - 5,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 1,3-benzenediamine whether or not with 3-aminopropyl terminated dimethylsilicones or dimethylsiloxanes (CAS RN 61128-46-9 and 99904-16-2), or - 5,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 1,4-benzenediamine (CAS RN 61128-47-0), or - 5,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 4,4'-sulfonylbis(benzenamine) (CAS RN 77699-82-2), or - 4,4'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), 5,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), 4,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), pyromellitic dianhydride, 1,2-benzenediamine, 1,3-benzenediamine and 1,4-benzenediamine with phthalic anhydride endcaps (CAS RN 96557-46-9), or - 4,4'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 4,4'-sulfonylbis(benzenamine) (CAS RN 1234673-19-8), or	S		Amendment	UNDER EXAMINATION	NL	Applicant	Round 2026-01 - request for amendment.//
---------------	----	--------------	------	-------	---	---	--	------------------	-------------------	----	-----------	--

ex 3920 99 28	50	3423/06 PROLONG 2022	5101	- 4,4'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 4,4'-(9H-fluoren-9-ylidene)bis[benzenamine] with phthalic anhydride endcaps (CAS RN 2803979-49-7) --- Current text: Polyetherimide of 4,4'-[(isopropylidene)bis(p-phenyleneoxy)]diphthalic dianhydride and 1,3-benzenediamine or 1,4-benzenediamine (CAS RN 61128-46-9 or CAS RN 61128-47-0)	S	Amendment	UNDER EXAMINATION	BE BE DE	Applicant Opposed Opposed	Round 2026-01 - objection.
ex 3921 19 00	60	1575341/2017 PROLONG 2023	5129	Multi-porous multilayer separator foil with: - one microporous polyethylene layer between two microporous polypropylene layers and whether or not containing a coating of aluminium oxide on both sides, - a width of 65 mm or more but not more than 170 mm, - a total thickness of 0,01 mm or more but not more than 0,03 mm,	S	Amendment	UNDER EXAMINATION	HU	Applicant	Round 2025-01 - review of the suspension + request change in classification, from CN 39211900 to CN 85079031.//

ex 7019 80 10	30	6663116/2024-1	5231	- a porosity of 0,25 or more but not more than 0,65 PL new proposal: Vacuum insulation panel, consisting of a gas-tight aluminum foil housing surrounding a rigid, air-free core with: - a glass wool filling, - a thickness of 5,6 mm or more but not more than 32,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than or equal to 2,5 mW/mK, - an internal pressure below 1,0 Pa, - an ambient temperature during operation of -50 °C or more but not more than 80 °C --- Current description: Vacuum insulation panel, consisting of a gas-tight aluminum foil housing surrounding a rigid, air-free core with: - a glass wool filling, - a thickness of 5,6 mm or more but not more than 32,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than 2,5 mW/mK, - an internal pressure of 0,1 Pa, - an ambient temperature during operation of -50 °C or more but not more than 70 °C	S	Amendment	UNDER EXAMINATION	PL	Applicant	Round 2026-01 request for amendment.//
---------------	----	----------------	------	---	---	------------------	-------------------	----	-----------	--

ex 7019 90 00	60	6663116/2024-2	5444	PL new proposal: Vacuum insulation panel, consisting of a gas-tight aluminium foil housing surrounding a rigid, air-free core with: - a glass fiber filling, - a thickness of 5,6 mm or more but not more than 32,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than or equal to 2,5 mW/mK, - an internal pressure below 1,0 Pa, - an ambient temperature during operation of -50 °C or more but not more than 80 °C *** Current description: Vacuum insulation panel, consisting of a gas-tight aluminium foil housing surrounding a rigid, air-free core with: - a glass fiber filling, - a thickness of 5,6 mm or more but not more than 32,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than 2,5 mW/mK, - an internal pressure of 0,1 Pa, - an ambient temperature during operation of -50 °C or more but not more than 70 °C	S	Amendment	UNDER EXAMINATION	PL	Applicant	Round 2026-01 request for amendment.// Round 2025/7 used for production of refrigerators, freezers and fridge-freezers
ex 8419 50 80	30	2132672/2024	5125	SK new proposal: Aluminium heat exchanger for gas boilers designed for heat transfer: - with a height of 100 mm or more, but	S	Amendment	UNDER EXAMINATION	SK	Applicant	Round 2026-01 - request for amendment.// Round 2025/01

ex 8483 50 80	20	4997528/2020	5224	not more than 150 mm, - with a width of 235 mm, but not more than 300 mm, - with a length of 240 mm or more, but not more than 300 mm, - for a power output of 25 kW or more, but not more than 35 kW, - with a weight of 8 kg or more, but not more than 10 kg --- Current description: Aluminium heat exchanger for gas boilers designed for heat transfer: - with a height of 100 mm or more, but not more than 120 mm, - with a width of 235 mm, but not more than 280 mm, - with a length of 250 mm or more, but not more than 280 mm, - for a power output of 25 kW or more, but not more than 35 kW, - with a weight of 8 kg or more, but not more than 10 kg	S	Amendment	UNDER EXAMINATION	HU	Applicant	Components for the energy industry.	Round 2026-01: request for amendment + prolongation item.//
---------------	----	--------------	------	---	---	------------------	-------------------	----	-----------	-------------------------------------	---

ex 8544 30 00 ex 8544 42 90	60 50	1233371/2015 PROLONG 2021	5123	SK new proposal: Four-core connecting cable containing two female connectors for the transmission of digital signals from navigation and/or audio systems to a USB connector and/or LCD monitor, for use in the manufacture of goods of Chapter 87	S	Amendment	UNDER EXAMINATION	SK	Applicant	Round 2026-01 - Request for amendment.//
ex 8708 40 20 ex 8708 40 50	70 60	5776455/2019 PROLONG 2025	5124	SK new proposal: Manual gearbox in cast aluminium housing for transverse installation with: - a width of not more than 550 mm, - a height of not more than 500 mm, - a length of not more than 600 mm, - five or six gears, - a differential gear, - an engine torque of 400 Nm or less, for use in the manufacture of motor vehicles	S	Amendment	UNDER EXAMINATION	CZ	Applicant	Round 2026-01 - request for amendment.//

ex 8708 40 20	80	5701899/2021	5131	of Heading 8703 --- Current description: Manual gearbox in cast aluminium housing for transverse installation with: - a width of not more than 480 mm, - a height of not more than 400 mm, - a length of not more than 550 mm, - five or six gears, - a differential gear, - an engine torque of 400 Nm or less, for use in the manufacture of motor vehicles of Heading 8703 (2)	S		Amendment	UNDER EXAMINATION	SE	Applicant	Round 2026-01 - request for amendment.//
				CZ new proposal: Transmission gearbox without torque converter, with: - dual clutch, - 7 or more forward gears, - 1 reverse gear, - a maximum torque of 450 Nm, - whether or not with electric motor integrated, - a height of 350 mm or more but not more than 600 mm, - a width 350 mm or more but not more than 600 mm, and - a weight of 70 kg or more but not more than 110 kg, for use in the manufacture of motor vehicles of Heading 8703 --- Current description: Transmission gearbox without torque converter, with: - dual clutch, - 7 or more forward gears, - 1 reverse gear,							

[illegible]

ex 8708 50 20 ex 8708 50 99	75 35	4702919/2018 PROLONG 2024 PROLONG 2025	5333	more than 595 mm, - a length of 410 mm or more but no more than 690 mm, for use in the manufacture of motor vehicles of subheadings 8703 40 and 8703 60 (2) PL new proposal: Constant velocity joint assembly for transmitting a torque from engine and transmission to wheels of motor vehicles, consisting of: - an inner race with 6 ball tracks or more but not more than 8 for running with the bearing balls with a diameter of 13,0 mm or more but not more than 28,0 mm, - an outer race with 6 ball tracks or more but not more than 8 for running with the bearing balls, made of steel with carbon content of 0,45 % or more but not more than 0,58 %, with thread and with a spline with 22 teeth or more but not more than 44, - a spherical cage keeping bearing balls in the ball tracks of outer race and inner race in proper angular position, made of material suitable for carburizing with carbon content of 0,14 % or more but not more than 0,55 %, and - with a grease compartment, - capable of working at constant speed at variable articulation angle not higher than 52 degrees --- Current description: Outboard joint assembly for transmitting a torque from engine and transmission to wheels of motor vehicles, consisting of: - an inner race with 6 ball tracks for	S	Amendment	UNDER EXAMINATION	PL	Applicant	Round 2026-01 - request for amendment.//
--------------------------------	----------	--	------	---	---	------------------	-------------------	----	-----------	--

ex 2917 19 80	55	5953671/2021	0902	Maleic acid (CAS RN 110-16-7) with a purity by weight of 99 % or more	S		Amendment	UNDER EXAMINATION	HU EU EU EU EU	Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension
ex 2920 90 10	15	1432061/2018	0903	Ethyl methyl carbonate (CAS RN 623-53-0)	S		Amendment	UNDER EXAMINATION	CZ EU EU EU EU	Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension
ex 2920 90 10	23	6580292/2023	0904	1,3,2-Dioxathiolane 2,2-dioxide (CAS RN 1072-53-3) with a purity by weight of 99 %, or more	S		Amendment	UNDER EXAMINATION	HU EU EU	Applicant Opposed Opposed	Round 2026-01 - review of the suspension
ex 2920 90 10	45	5899366/2021	0905	Ethylene carbonate (CAS RN 96-49-1) with a purity by weight of 99 % or more	S		Amendment	UNDER EXAMINATION	HU EU EU EU EU	Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension
ex 2920 90 10	55	5899407/2021	0906	Vinylene carbonate (CAS RN 872-36-6) with a purity by weight of 99,9 % or more	S		Amendment	UNDER EXAMINATION	HU EU EU EU EU	Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension.//
ex 2920 90 10	65	5899447/2021	0907	Vinyl ethylene carbonate (CAS RN 4427-96-7) with a purity by weight of 99 % or more	S		Amendment	UNDER EXAMINATION	HU EU EU EU EU	Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension.//
ex 2920 90 10	85	6705077/2022	0908	Diethyl carbonate (CAS RN 105-58-8) with a purity by weight of 99,9 % or more	S		Amendment	UNDER EXAMINATION	HU EU EU EU	Applicant Opposed Opposed Opposed	Round 2026-01 - review of the suspension.//
ex 3824 99 92	22	1957046/2022	0909	Solution containing: - 30 % or more but not more than	S		Amendment	UNDER EXAMINATION	CZ EU	Applicant Opposed	Round 2026-01 - review of the suspension

ex 3824 99 92	52	1697432/2019	0910	40 % by weight of lithium hexafluorophosphate (CAS RN 21324-40-3), and - 60 % or more but not more than 70 % by weight of ethyl methyl carbonate (CAS RN 623-53-0), or dimethyl carbonate (CAS RN 616-38-6)	S	Amendment	UNDER EXAMINATION	PL EU EU EU EU	Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension	suspension
ex 3824 99 92	71	6597948/2023	0911	Electrolyte containing: - 5 % or more but not more than 20 % lithium hexafluorophosphate (CAS RN 21324-40-3) or lithium tetrafluoroborate (CAS RN 14283-07-9), - 60 % or more but not more than 90 % of a mixture of ethylene carbonate (CAS RN 96-49-1), dimethyl carbonate (CAS RN 616-38-6) and/or ethyl methyl carbonate (CAS RN 623-53-0), - 0,5 % or more but not more than 20 % 1,3,2-dioxathiolane 2,2-dioxide (CAS RN 1072-53-3), for use in the manufacture of motor vehicle batteries (1)	S	Amendment	UNDER EXAMINATION	HU EU EU	Applicant Opposed Opposed	Round 2026/01 - review of the measure.	
ex 3921 19 00 8507 90 31	40	3938612/2015	0912	Mixture containing by weight: - 49 % or more but not more than 51 % of ethylene carbonate (CAS RN 96-49-1), and - 49 % or more but not more than 51 % of 1,3-propanesultone (CAS RN 1120-71-4) Transparent, microporous, acrylic acid grafted polyethylene film, in the form of rolls, with:	S	Amendment	UNDER EXAMINATION	FR EU	Applicant Opposed	Round 2025-01 - review of the suspension + request	

ex 3921 19 00 8507 90 31	45	1489232/2017	0913	- a width of 98 mm or more but not more than 170 mm, - a thickness of 15 µm or more but not more than 36 µm, of a kind used for the manufacture of alkaline battery separators	S	Amendment	UNDER EXAMINATION	DE EU	Applicant Opposed	change in classification, from CN 39211900 to CN 85079031.// Round 2025-01 - review of the suspension + request change in classification, from CN 39211900 to CN 85079031.// Round 2025-01 - review of the suspension Round 2024-01 - review of the suspension Round 2023-01 - review of the suspension Round 2022-01: Review of the measure. Round 2021-01: Amendment. 3.2% duty installed.Old Taric code 39211900 (80), new TARIC code 39211900(45). ROUND 2018-01 Zink-Luft-Knopfzellen, Lithium-Ion Zellen	change in classification, from CN 39211900 to CN 85079031.//
ex 8507 60 00	15	1144451/2015	0914	Cylindrical lithium-ion-accumulators or modules with: - a nominal capacity of 8,8 Ah or more, but not more than 18 Ah, - a nominal voltage of 36 V or more, but not more than 48 V, - a power of 300 Wh or more, but	S	Amendment	UNDER EXAMINATION	AT NL EU EU	Applicant Co-applicant Opposed Opposed	Round 2026-01 - review of the suspension.//	

ex 8507 60 00	18	4793865/2018	0915	not more than 648 Wh, for use in the manufacture of electric bicycles (1)	S Lithium-ion polymer accumulator pack equipped with a battery management system and can-bus interface with: - 6 modules with 90 cells or more but not more than 192 cells, - a nominal voltage of 280 V or more but not more than 400 V, - a nominal capacity of 9,7 Ah or more but not more than 120 Ah, - a charging voltage of 110 V or more but not more than 495 V, and in a metal casing with: - a length of not more than 1 723 mm, - a width of not more than 1 162,23 mm, - a height of not more than 395 mm, for use in the manufacture of vehicle capable of being charged by plugging to external source of electric power of heading 8703 (1)	Amendment	UNDER EXAMINATION	SE EU	Applicant Opposed	Round 2026-01 - review of the suspension.//
ex 8507 60 00	21	2037672/2023	0916	Cylindrical rechargeable lithium-ion polymer accumulator module with: - a cable, - a connector, - 1 or 2 cells, - a charge control module or NTC temperature sensor, - a fuse, - a weight of 37,3 g or more but not more than 91,5 g, - a nominal voltage of 3,2 V, - a battery capacity of 1 100 mAh or more but not more than 2 200 mAh,	S Cylindrical rechargeable lithium-ion polymer accumulator module with: - a cable, - a connector, - 1 or 2 cells, - a charge control module or NTC temperature sensor, - a fuse, - a weight of 37,3 g or more but not more than 91,5 g, - a nominal voltage of 3,2 V, - a battery capacity of 1 100 mAh or more but not more than 2 200 mAh,	Amendment	UNDER EXAMINATION	HU EU EU	Applicant Opposed Opposed	Round 2026-01 - review of the suspension.//

ex 8507 60 00	24	2102065/2023			for the manufacture of automatic emergency call devices for passenger cars (1)	Rechargeable lithium-ion battery, based on lithium-iron-phosphate technology, with: - a fuse, - a cell-to-pack design, - a length of 985 mm or more but not more than 1 015 mm, - a width of 1 050 mm or more but not more than 1 070 mm - a height of 145 mm or more but not more than 160 mm, - a weight of 220 kg or more but not more than 250 kg, - a capacity of 200 Ah or more, - a specific energy density of 130 Wh/kg or more, for use in the manufacture of vehicles of subheading 8702 40 (1)	S	Amendment	UNDER EXAMINATION	NL EU EU	Applicant Opposed Opposed	Round 2026-01 - review of the suspension.//
ex 8507 60 00	26	6609698/2023		0918		Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with: - a length of 670 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, - a height of 110 mm or more, but not more than 137 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not more than 29 360 Wh	S	Amendment	UNDER EXAMINATION	DE EU EU EU	Applicant Opposed Opposed Opposed	Round 2026/01 review of the measure.//
ex 8507 60 00	28	6598010/2023		0919		HU new proposal: Lithium-ion rechargeable battery cell with:	S	Amendment	UNDER EXAMINATION	SK EU	Applicant Opposed	Round 2026-01 - review of the measure + request for

ex 8507 60 00	29	1961285/2022	0920	- a length of 190 mm or more but not more than 380 mm, - a width of 90 mm or more but not more than 150 mm, - a height of 4 mm or more but not more than 35 mm, - a weight of 0,1 kg or more but not more than 2,5 kg, - a nominal voltage of 3,0 VDC or more but not more than 5,0 VDC, - a nominal capacity of not more than 150 Ah, for use in the manufacture of rechargeable hybrid and electric vehicle batteries *** Current description: Lithium-ion rechargeable battery cell with: - a length of 190 mm or more but not more than 380 mm, - a width of 90 mm or more but not more than 150 mm, - a height of 4 mm or more but not more than 15 mm, - a weight of 0,1 kg or more but not more than 1,2 kg, - a nominal voltage of 3,0 VDC or more but not more than 4,0 VDC, - a nominal capacity of not more than 90 Ah, for use in the manufacture of rechargeable hybrid and electric vehicle batteries (1)	S	Amendment	UNDER EXAMINATION	DE EU EU	Applicant Opposed Opposed	Round 2026-01 - review of the suspension.//	amendment.//
---------------	----	--------------	------	--	---	-----------	-------------------	----------------	---------------------------------	---	--------------

ex 8507 60 00	30	1572/14/1995 PROLONG 2015 PROLONG 2023	0921	Cylindrical lithium-ion accumulator or module, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (1)	S	Amendment	UNDER EXAMINATION	IE EU EU EU	Opposed Opposed		Round 2026-01 - review of the suspension
ex 8507 60 00	33	1232310/2015	0922	Lithium-ion battery module or accumulator, with: - a length of 150 mm or more, but not more than 1 310 mm, - a width of 100 mm or more, but not more than 1 000 mm, - a height of 200 mm or more, but not more than 1 500 mm, - a weight of 50 kg or more, but not more than 200 kg, - cells of a nominal capacity of 58 Ah or more but not more than 500Ah, - a nominal output voltage of 230 V AC or 45 V or more but not more than 980 V DC	S	Amendment	UNDER EXAMINATION	NL EU EU EU EU	Applicant Opposed Opposed Opposed Opposed		Round 2026-01:review of the suspension.//
ex 8507 60 00	36	6609601/2023	0923	Lithium-ion accumulator, with - multiple connected lithium-ion accumulator cells, - charging and monitoring electronics,	S	Amendment	UNDER EXAMINATION	DE EU EU	Applicant Opposed Opposed		Round 2026-01 review of the suspension.//

ex 8507 60 00	38	323555/2012	0924		- a power of 74 Wh or more, but not more than 75 Wh, - in a plastic housing with electrical connection contacts and LCD display, for use in the manufacture of cordless vacuum cleaners or rechargeable power sources therefor (1)	S	Amendment	UNDER EXAMINATION	FR DE SE EU EU EU EU EU PL	Applicant Co-applicant Co-applicant Opposed Opposed Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension.//
ex 8507 60 00	48	4922932/2020	0925		Integrated battery system in a metal or plastic case with or without holders, consisting of: - a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy between 0,3kWh and 0,9 kWh, - a Battery Management System, - a power relay, - a cooling system, - one to four connectors, for use in the manufacture of Mild-hybrid (mHEV) motor vehicles (1)	S	Amendment	UNDER EXAMINATION	CZ EU EU EU EU	Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension.
ex 8507 60 00	58	4697852/2018	0926		Prismatic lithium-ion electric accumulator with:	S	Amendment	UNDER EXAMINATION	PL DE	Applicant Co-applicant	Round 2026-01 - review of the

ex 8507 60 00	68	5988869/2019	0927	- a width of 120,0 mm or more but not more than 305,0 mm, - a thickness of 12,0 mm or more but not more than 67,0 mm, - a height of 72,0 mm or more but not more than 126,0 mm, - a nominal voltage of 3,6 V or more but not more than 3,75 V, and - a nominal capacity of 6,9 Ah or more not more than 265 Ah, for use in the manufacture of rechargeable electric vehicle batteries (1)	S	Amendment	UNDER EXAMINATION	DE EU EU EU EU	Opposed Opposed Opposed Opposed	suspension Round 2025-01 - review of the suspension
				- a length of 65 mm or more, but not more than 225 mm, - a width of 10 mm or more, but not more than 75 mm, - a height of 60 mm or more, but not more than 285 mm, - a nominal voltage of 2,1 V or more, but not more than 3,8 V, and - a nominal capacity of 2,5 Ah or more, but not more than 325 Ah					Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension
ex 8507 60 00	77	1095345/2012	0928	Lithium-ion rechargeable batteries, with: - a length of 700 mm or more, but not more than 2 820 mm, - a width of 935 mm or more, but not more than 1 660 mm, - a height of 85 mm or more, but not more than 700 mm, - a weight of 250 kg or more, but not more than 700 kg, - a power of not more than 175 kWh, - a nominal voltage of 320 V or more, but not more than 430 V	S	Amendment	UNDER EXAMINATION	NL ES EU EU EU	Applicant Co-applicant Opposed Opposed Opposed	Round 2026-01 - review of the suspension.//

ex 8507 60 00	83	5691842/2021	0929	Modules for the assembly of lithium-ion electric accumulators with: - a length of 570 mm or more, but not more than 610 mm, - a width of 210 mm or more, but not more than 240 mm, - a height of 100 mm or more, but not more than 125 mm, - a weight of 28 kg or more, but not more than 35 kg, and - a capacity of not more than 2500 Ah and a nominal energy of less than 8,4 kW, for use in the manufacture of vehicles of subheadings 8703 60, 8703 70, 8703 80 and 8704 60 (1)	S	Amendment	UNDER EXAMINATION	DE EU EU EU	Applicant Opposed Opposed Opposed	Round 2026-01 - review of the suspension
ex 8507 90 80	55	2207294/2022	0930	Top cap or housing made of aluminium or ferrous alloy or stainless steel: - whether or not including parts made of aluminium and aluminium alloy, - with or without sealing elements or other elements made of polymer material, - with or without a "current interrupt device" and an "evacuation valve" - with or without plastic sockets - with an outer diameter of 17 mm or more, but not more than 18 mm, or rectangular with: - length not greater than 450 mm, - width not greater than 200 mm, and - height not greater than 150 mm, for use in the manufacture of lithium-ion batteries (1)	S	Amendment	UNDER EXAMINATION	DE TR EU EU EU EU	Applicant Applicant Opposed Opposed Opposed Opposed	Round 2026-01 - review of the suspension.//
ex 8536 41 90	60	1398260/2024	0931	Power relay with the function of safely connecting or disconnecting the charging	S	Amendment	UNDER EXAMINATION	SK EU	Applicant Opposed	Round 2026/1 Review of the suspension.//

